



**S80 & A80 custom-made overhead doors,
an optimally insulated quality solution for every facade**



Custom-made quality!

The insulation value of an 80-mm door is considerably higher than that of a 40-mm door. Moreover, the panels are thermally separated. Practice shows that on average a door is closed more than 90% of the time. A particularly well insulated door leads to considerable energy savings and is as such a socially responsible choice.

S80

When developing and building modern company halls, insulation is an important factor! It is logical that, for instance, 100-mm steel sandwich panels are chosen for both the walls and the roofing. If 40-mm doors are installed in such a hall, all of these investments are not as profitable as they could be. After all, heat exits the building through the weakest link. Our S80 has the same options as the 40-mm door, but offers a higher insulation value, therefore

the S80 is a fully-fledged alternative for a 40-mm door.

The S80 is available in three standard RAL colours: RAL 9002, RAL 9006 and RAL 7016. Of course, every door can be manufactured in any desired RAL colour. The outer leaf is embossed.

The panels are thermally separated and are as a result produced without finger protection.

A80 – Quadruple glazing in 80-mm aluminium door

The 80-mm aluminium sections are as standard anodised and fitted with quadruple glazing. A80 sections are always POWDER COATED if you order the door in a colour. The A80 sections feature thermal separation and are executed without finger protection.

A80

The A80 is an excellent alternative for the 40-mm version. Is daylight on the work floor a requirement and do you want to retain the planned insulation value? Then the A80 is a perfect solution. In addition to the light transmission and the high insulation value, the A80 overhead door offers sufficient opportunities to match it to the building. The A80 can also be used as a section in an S80. An A80 door combined with an S80 bottom section is used frequently.



Below is a summary of various technical details and options that can help you make the right choice. Both the S80 and the A80 doors meet all applicable technical CE standards.

The 80-mm range

S80 steel sandwich 80 mm, thermally separated*

A80 aluminium 80 mm with quadruple glazing, thermally separated*

Pass door, available for both the A80 and S80

* = NO thermal bridge



Pass door possible

As the first and only door manufacturer, we can supply pass doors for 80-mm doors. Pass doors can be fitted to both the S80 and A80. For both the S80 and the A80, the pass door is only available in combination with the low threshold.

A pass door offers many advantages. And the use of a low threshold makes it usable in even more situations. What is unique is that we have managed to retain all of the characteristics of the 40-mm pass door in the 80-mm door. As a result, both the S80 and the A80 are perfect alternatives if insulation is of decisive importance.

Heat loss images

The images below were made with a special thermal imaging camera. They clearly show the difference between the insulation values of the S40 and the S80.



DMB/TLB/DLW/LDB 4000 mm x DMH/TLH/DLH/HDB 4000 mm					
	S40 - U Value	S80 - U Value	Improved insulation	Saving fuel oil*	Saving gas*
Blank sections	1,33	0,73	82%	73 ltr	100 m
Blank sections with 1 section with 4 click windows	1,46	0,77	89%	83 ltr	114 m ³
Blank sections with 2 sections with 4 click windows	1,59	0,81	96%	94 ltr	129 m ³
DMB/TLB/DLW/LDB 4000 mm x DMH/TLH/DLH/HDB 4000 mm					
	S40/A40 - U Value 2V	S80/A80 - U Value 4V	Improved insulation	Saving fuel oil*	Saving gas*
Blank sections with 1 glass section	1,69	0,91	85%	94 ltr	130 m ³
Blank sections with 2 glass sections	2,03	1,10	84%	112 ltr	154 m ³
DMB/TLB/DLW/LDB 4000 mm x DMH/TLH/DLH/HDB 4000 mm					
	A40 nieuw - U Value 2V	A40 nieuw - U Value 3V	Improved insulation	Saving fuel oil*	Saving gas*
PMMA windows standard	3,69	3,01	22%	82 ltr	113 m ³
DMB/TLB/DLW/LDB 4000 mm x DMH/TLH/DLH/HDB 4000 mm					
	A40 nieuw - U Value 2V	A80 - U Value 4V	Improved insulation	Saving fuel oil*	Saving gas*
PMMA windows standard	3,69	2,17	70%	184 ltr	253 m ³

* Annual savings / 10°C temperature difference

Calculated according to EN 13241 / EN 12428 / EN 673 and underlying relevant standards